

DHI-ARK30T-W2

Wireless Keypad



System Overview

Wireless Keypad is used with Alarm Hub, and supports multiple users, allowing each one to access the alarm security system with their own private passcode. The system also conveniently keeps a log of the operations performed by each user, making it easy to review and analyze usage history.

Scene

Ideal for use in villas, shops, apartments and more.

Technical Specification

Function

Indicator Light	4 indicators (communication, arm/disarm, fault, and alarm)	
Button	15 buttons (0–9, *, #, arm, disarm, and home arm)	
Buzzer	1 × built-in buzzer	
Arm and Disarm	Password; IC card	
Remote Update	Cloud update	
Low Battery Detection	Yes	
Tamper	Yes	
Measuring Range (Temperature)	–15 °C to +65 °C (+5 °F to +149 °F) (indoor)	
Measuring Accuracy	1 °C (33.8 °F)	
User Management	32 users	

Wireless

Carrier Frequency	433.1 MHz-434.6 MHz
Communication Mechanism	Two-way

- · Supports 3 shortcut alarms: Medical, fire, emergency.
- · Arm/Disarm with password or IC card.
- Supports signal strength detection to select suitable installation sites.
- · Low battery alarm.
- Temperature measurement.
- Frequency hopping function and two-way communication.
- Cloud update and automatic recovery from update failure.


Communication Distance	Up to 1,200 m (3,937.01 ft) in an open space
Encryption Mode	AES128
Frequency Hopping	Yes

General

4 × AA batteries	
3 years (if the device is used to arm and disarm	
once a day)	
Max. 2.3 W	
$-10~^{\circ}\text{C}$ to +55 $^{\circ}\text{C}$ (+14 $^{\circ}\text{F}$ to +131 $^{\circ}\text{F}$) (indoor)	
10%-90% (RH)	
146.0 mm × 82.0 mm × 22.6 mm (5.75" × 3.23" × 0.89")	
,	
180.0 mm × 104.0 mm × 58.0 mm (7.07" × 4.09" × 2.28")	
240 g (0.529 lb) (with battery)	
145 g (0.32 lb) (without battery)	
370 g (0.816 lb)	
Wall mount	
PC + ABS	
CF	

Ordering Information				
Туре	Part Number	Description		
Keypad	DHI-ARK30T-W2	Wireless Keypad		

Installation



Application







Alarm Hub

Dimensions (mm[inch])

