

# VTH5221E(W)-H

IP Indoor Monitor





Technical Specification	
Model	VTH5221E(W)-H
System	
Main Processor	Embedded Micro Processor
Operation System	Embedded LINUX OS
Video	
Video Compression	H.264
Audio	
Audio Compression	G.711
Audio Input	All-direction Microphone
Audio Output	Built-in Loudspeaker
Bidirectional Talk	Support Dual-way Bidirectional talk
Display	
LCD Screen	7" 1024x600, Capacitive
Operation Mode	
Input	Touch buttons
Interface	
Alarm In	6
RS485	1
Network	
Ethernet	10M/100Mbps Self-adaptive
Network Protocol	TCP/IP
General	
Memory Slot	Micro SD, Max 32GB

- 7" TFT Capacitive touch screen, 1024x600
- · IPC surveillance
- · Alarm integration
- $\cdot$  Micro SD card optional, max 32GB
- · Record & Snapshot(SD card needed)





















Installation	Surface & Desktop
Power	DC 12V, PoE(802.3af)
Power Consumption	Standby ≤3.5W, Work ≤5W
Working Temperature	-10°C~+55°C
Relative Humidity	10%~90%RH
Dimensions	236mm×165.5mm×43.2mm
Weight	0.9Kg

### **Dimensions**

# View Area





# Application

