

DH-PFM344D-20CH-EN

Switching Power Supply



Series Overview

Dahua Switching Power Supply meets both national and regional certificate requirements. It offers outstanding performance, makes reliable use of electricity and is efficient, stable and environmentally friendly. The power supply comes with overload protection and overvoltage protection, and can be widely used in the security industry.

Technical Specification		
Function		
Input Voltage	100 VAC-240 VAC	
Output Voltage	Normal: 12 VDC Long: 13.5 VDC Ex-Long: 15 VDC	
Rated Output Current	Normal: 5 A Long: 4.5 A Ex-Long: 4 A	
Rated Power	Output power: 12 W (for one channel) Total power: 60 W	
Power Consumption In Idle	≤0.21 W	
Efficiency	≥88%	
Port		
Input Port	2-core female seat C8, with European standard cable	
Output Plug	20 channel output terminal	
Protection		
Types of Protection	Overcurrent protection, short circuit protection and overvoltage protection	
Surge Protection Grade	Common mode: ±4 kV Differentiate mode: ±2 kV	

- Outputs through 20 channels and can supply to multiple devices at the same time.
- The output voltage can be adjusted to 3 levels, making it easily adapt to various types of devices.
- Easy to install, the device supports wall mount installation.
- Designed with protection against overcurrent, overvoltage, and short circuits.
- Surge protection: common mode: ±4 kV, differentiate mode: ±2 kV.
- · V-0 fireproof.
- · CE certification.
- · Efficiency Level: VI

Statics Protection	Air discharge: ±8 kV Contact discharge: ±6 kV	
Structure		
Installation	Wall mount	
Product Dimensions	158.0 mm × 104.0 mm × 34 mm (6.22" × 4.10" × 1.34") (L × W × H)	
Appearance Color	Gray	
Net Weight	0.31 kg (0.68 lb)	
Input Cable Length	1000 mm (39.37")	
Environment		
Operating Temperature	0 °C to +40 °C (+32 °F to +104 °F)	
Operating Humidity	10%-90% (RH)	
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)	
Storage Humidity	5%-95% (RH)	
Certifications		
Certifications	CE	

Ordering Information			
Туре	Model	Description	
Switching Power Supply	DH-PFM344D-20CH-EN	Switching Power Supply	

Dimensions (mm[inch])

mm [inch]

